

A VERSATILE WALLCOVERING SYSTEM

MAKE IT SMOOTH WITH **OVERLAY™**



Goes on Easily,  
Finishes Perfectly

For walls that truly are smooth as glass, choose Vitruan Overlay. Made of 100 percent glass filaments, Overlay is a non-woven wallcovering that creates a flush, clean surface designed to hide imperfections of your walls. It's simple to apply and even easier to maintain. Overlay goes on like regular wallpaper, and can then be painted in any color. The result is a seamless surface that can be cleaned and scrubbed as needed. Plus it can be repainted over and over, while still maintaining its sleek aesthetics.

[vitruanusa.com](http://vitruanusa.com)



*Overlay is easy to apply and corrects imperfections*



*Overlay creates an easy-to-paint surface for the color of your choice*

Ger-Eck, LLC  
Exclusive Distributors of Vitrulan Glass Textile Products  
10317 Johns Towne Drive Charlotte, NC 28210  
for more info: [g.griffin@vitrulanusa.com](mailto:g.griffin@vitrulanusa.com)

[www.vitrulanusa.com](http://www.vitrulanusa.com)

### OVERLAY FEATURES & BENEFITS

- Offers optimal hiding capacity, covering wall imperfections and providing a smooth finish.
- Reinforces the substrate, creating a paintable, high-performance surface.
- Works well when wet and won't tear during installation.
- Simplifies seaming, making installation easy.
- Cuts easily, without any compression, creasing or marks.
- Works well in even the tightest of corners.
- Provides an environmentally friendly choice that's Oko-Tex and LEED certified.

### OVERLAY PRODUCT SPECIFICATIONS

|                                      |                                                                                  |
|--------------------------------------|----------------------------------------------------------------------------------|
| Material:                            | e-glass (chopped filaments)                                                      |
| Binder:                              | Duroplast, not affected by water                                                 |
| Weight: [oz. per yard <sup>2</sup> ] | e5.9 (200 g/m <sup>2</sup> )                                                     |
| Filament diameter [microns]          | 6.5 um                                                                           |
| Thickness: [Inch]                    | 0.012 (0.3 mm)                                                                   |
| Tensile strength [ lbs. /inch]       | Vertical direction: 34 (300 N / 5 cm)<br>Horizontal direction: 29 (250 N / 5 cm) |
| Elongation: [%]                      | Vertical: 2 Horizontal: 2                                                        |
| Roll Width: [inches]                 | 39.4" (100cm)                                                                    |
| Roll length: [yards]                 | 54.7 (50 m)                                                                      |